



高銹電率陶瓷電容器

HIGH DIELECTRIC CONSTANT CERAMIC CAPACITOR

TEMP. COEFF. / CAP VALUE / RATED VOLTAGE

溫度特性 TC	額定電壓 V.DC	容量範圍 CAPACITANCE		尺寸 size	
		電容量(pF)	誤差(TOL)	直徑(D)	厚度(T)
Y5P (B)	50V.DC	100~2200	K	5	3
		2400~3300	K	6	3
		3600~6800	K	7	3
		8200~10000	K	8	3
	250V.DC	100~2200	K	5	4
		2400~3300	K	7	4
		3600~4700	K	9	4
		6800~10000	K	10	4
	500V.DC	100~2200	K	5	4
		2400~3300	K	7	4
		3600~4700	K	9	4
		6800~10000	K	10	4
Y5U (E)	50V.DC	1000~6800	M	5	4
		8200~10000	M	6	4
		12000~68000	M	7	4
		82000~100000	M	8	4
	250V.DC	1000~6800	M	5	4
		8200~10000	M	7	4
		12000~22000	M	9	4
		30000~33000	M	10	4
	500V.DC	1000~6800	M	5	4
		8200~10000	M	7	4
		12000~22000	M	9	4
		30000~33000	M	10	4
Y5V (F)	50V.DC	1000~10000	M,Z	5	4
		12000~22000	M,Z	6	4
		30000~33000	M,Z	7	4
		47000~100000	M,Z	8	4
		220000	Z	10	4
	250V.DC	1000~10000	M,Z	5	4
		12000~47000	M,Z	7	4
		68000~82000	M,Z	9	4
		100000	M,Z	10	4
	500V.DC	1000~10000	M,Z	5	4
		12000~47000	M,Z	7	4
		68000~82000	M,Z	9	4
100000		M,Z	10	4	