



半導體陶瓷電容器

SEMI-CONDUCTIVE CERAMIC CAPACITOR

TEMP. COEFF./CAP VALUE/RATED VOLTAGE

溫度特性 TC	額定電壓 V.DC	容量範圍 CAPACITANCE		尺寸 SIZE	
		電容量(pF)	誤差(TOL)	直徑(D)	厚度(T)
Y5P	16V.DC	10000	K M	5	3.0
		15000~27000	K M	6	3.0
		33000	K M	7	3.0
		47000~56000	K M	8	3.0
		68000	K M	9	3.0
		100000	K M	10	3.0
	25V.DC	10000	K M	5	3.0
		15000~27000	K M	6	3.0
		33000	K M	7	3.0
		47000~56000	K M	8	3.0
		68000	K M	9	3.0
		100000	K M	10	3.0
	50V.DC	10000	K M	5	3.0
		15000~27000	K M	6	3.0
		33000	K M	7	3.0
		47000~56000	K M	8	3.0
		68000	K M	9	3.0
		100000	K M	10	3.0
Y5U	16V.DC	10000	M	6	3.0
		15000~22000	M	5	3.0
		27000~56000	M	6	3.0
		68000~100000	M	8	3.0
	25V.DC	10000	M	6	3.0
		15000~22000	M	5	3.0
		27000~56000	M	6	3.0
		68000~100000	M	8	3.0
	50V.DC	10000	M	6	3.0
		15000~22000	M	5	3.0
		27000~56000	M	6	3.0
		68000~100000	M	8	3.0
Y5V	16V.DC	10000~47000	Z	5	3.0
		56000~68000	Z	6	3.0
		100000	Z	7	3.0
		200000~330000	Z	10	3.0
	25V.DC	10000~47000	Z	5	3.0
		56000~68000	Z	6	3.0
		100000	Z	7	3.0
		200000~330000	Z	10	3.0
	50V.DC	10000~47000	Z	5	3.0
		56000~68000	Z	6	3.0
		100000	Z	7	3.0
		200000~220000	Z	10	3.0