





片式鋁電解電容

CHIP TYPE ALUMINUM ELECTROLYTIC CAPACITORS

■ 尺寸圖 Dimensions



	(mm)					
	4 X 5.4	5 X 5.4	6.3 X 5.4	6.3 X 7.7	8 X 10.5	10 X 10.5
A	1.8	2.1	2.4	2.4	2.9	3.2
B	4.3	5.3	6.6	6.6	8.3	10.3
C	4.3	5.3	6.6	6.6	8.3	10.3
E	1.0	1.3	2.2	2.2	3.1	4.5
L	5.4	5.4	5.4	7.7	10.5	10.5
H	0.5~0.8			0.8~1.1		

◆ 標稱電容量、額定電壓、額定紋波電流與外形尺寸對應表

Nominal capacitance, rated voltage, rated ripple current and case size table

V	4		6.3		10		16		25		35		50		63		100	
	DXL mm	1~mA	DXL mm	1~mA	DXL mm	1~mA	DXL mm	1~mA	DXL mm	1~mA	DXL mm	1~mA	DXL mm	1~mA	DXL mm	1~mA	DXL mm	1~mA
0.1													4X5.4	1.0	4X5.4	1.0		
0.22													4X5.4	2.0	4X5.4	2.3		
0.33													4X5.4	2.8	4X5.4	3.5		
0.47													4X5.4	4.0	4X5.4	5.0		
1.0													4X5.4	8.4	4X5.4	10		
2.2													4X5.4	13	4X5.4	15		
3.3													4X5.4	17	4X5.4	20	6.3X7.7	28
4.7									4X5.4	16	4X5.4	18	4X5.4	18	4X5.4	23	6.3X7.7	35
10							4X5.4	23	4X5.4	24	4X5.4	24	5X5.4	30	6.3X5.4	34	6.3X7.7	50
22			4X5.4	28	4X5.4	30	4X5.4	30	5X5.4	38	5X5.4	39	6.3X5.4	43	6.3X7.7	70	8 X 10.5	120
33	4X5.4	28	4X5.4	34	4X5.4	34	5X5.4	44	5X5.4	48	6.3X5.4	53	6.3X7.7	85	8 X 10.5	160	10X10.5	190
47	4X5.4	33	4X5.4	40	5X5.4	47	5X5.4	52	6.3X5.4	60	6.3X7.7	70	6.3X7.7	90	8 X 10.5	170		
56	5X5.4	42	5X5.4	46	6.3X5.4	52	6.3X5.4	58	6.3X7.7	65	6.3X7.7	80	8 X 10.5	150	8 X 10.5	230		
100	5X5.4	56	5X5.4	47	5X5.4	54	6.3X5.4	86	6.3X7.7	130	6.3X7.7	120	8 X 10.5	181	8 X 10.5	280		
150	6.3X5.4	79	6.3X5.4	70	6.3X5.4	76					10X10.5	175	10X10.5	195				
220	6.3X5.4	96	6.3X7.7	95	6.3X7.7	150	6.3X7.7	150	8 X 10.5	215	8 X 10.5	232	8 X 10.5	246	10X10.5	289		
330	6.3X7.7	152	6.3X7.7	150	8 X 10.5	240	8 X 10.5	270	8 X 10.5	284	10X10.5	305	10X10.5	324				
470	6.3X7.7	200	8 X 10.5	265	8 X 10.5	290	8 X 10.5	307	10X10.5	393								
680	8 X 10.5	284	8 X 10.5	318	10X10.5	374	10X10.5	396										
1000	8 X 10.5	344	8 X 10.5	372	10X10.5	400												
1500	10X10.5	347	10X10.5	489														

I~ = Rated ripple current (mA) (85°C, 120Hz) I~ = 額定紋波電流 (mA) (85°C, 120Hz)